§51.52

Data supporting this table are given in the "Environmental Survey of the Uranium Fuel Cycle," WASH–1248, April 1974; the "Environmental Survey of the Reprocessing and Waste Management Portion of the LWR Fuel Cycle," NUREG–0116 (Supp.1 to WASH–1248); the "Public Comments and Task Force Responses Regarding the Environmental Survey of the Reprocessing and Waste Management Portions of the LWR Fuel Cycle," NUREG–0216 (Supp. 2 to WASH–1248); and in the record of the final rulemaking pertaining to Uranium Fuel Cycle Impacts from Spent Fuel Reprocessing and Radioactive Waste Management, Docket RM–50–3. The contributions from reprocessing, waste management and transportation of wastes are maximized for either of the two fuel cycles (uranium only and no recycle). The contribution from transportation excludes transportation of cold fuel to a reactor and of irradiated fuel and radioactive wastes from a reactor which are considered in Table S–4 of §51.20(g). The contributions from the other steps of the fuel cycle are given in columns A–E of Table S–3A of WASH–1248.

2The contributions to temporarily committed land from reprocessing are not prorated over 30 years, since the complete temporary impact accrues regardless of whether the plant services one reactor for one year or 57 reactors for 30 years.

3Estimated effluents based upon combustion of equivalent coal for power generation.

41.2 percent from natural gas use and process.

41.2 percent from natural gas use and process.

149 FR 9381 Mar 12 1984: 49 FR 10922 Mar 23 1984 as amended at 67 FR 77652 Dec. 19 20021

§51.52 Environmental effects of transportation of fuel and waste—Table S-4.

Every environmental report prepared for the construction permit stage of a light-water-cooled nuclear power reactor, and submitted after February 4, 1975, shall contain a statement concerning transportation of fuel and radioactive wastes to and from the reactor. That statement shall indicate that the reactor and this transportation either meet all of the conditions in paragraph (a) of this section or all of the conditions in paragraph (b) of this sec-

- (a)(1) The reactor has a core thermal power level not exceeding megawatts:
- (2) The reactor fuel is in the form of sintered uranium dioxide pellets having a uranium-235 enrichment not exceeding 4% by weight, and the pellets are encapsulated in zircaloy rods;
- (3) The average level of irradiation of the irradiated fuel from the reactor does not exceed 33,000 megawatt-days per metric ton, and no irradiated fuel assembly is shipped until at least 90 days after it is discharged from the reactor.
- (4) With the exception of irradiated fuel, all radioactive waste shipped from

the reactor is packaged and in a solid form:

- (5) Unirradiated fuel is shipped to the reactor by truck; irradiated fuel is shipped from the reactor by truck, rail, or barge; and radioactive waste other than irradiated fuel is shipped from the reactor by truck or rail; and
- (6) The environmental impacts of transportation of fuel and waste to and from the reactor, with respect to normal conditions of transport and possible accidents in transport, are as set forth in Summary Table S-4 in paragraph (c) of this section; and the values in the table represent the contribution of the transportation to the environmental costs of licensing the reactor.
- (b) For reactors not meeting the conditions of paragraph (a) of this section, the statement shall contain a full description and detailed analysis of the environmental effects of transportation of fuel and wastes to and from the reactor, including values for the environmental impact under normal conditions of transport and for the environmental risk from accidents in transport. The statement shall indicate that the values determined by the analysis represent the contribution of such effects to the environmental costs of licensing the reactor.

(c)

SUMMARY TABLE S-4-ENVIRONMENTAL IMPACT OF TRANSPORTATION OF FUEL AND WASTE TO AND FROM ONE LIGHT-WATER-COOLED NUCLEAR POWER REACTOR 1

Normal Conditions of Transport

	Environmental impact
Heat (per irradiated fuel cask in transit)	250,000 Btu/hr. 73,000 lbs. per truck; 100 tons per cask per rail car.
Truck	Less than 1 per day. Less than 3 per month

Nuclear Regulatory Commission

Exposed population	Estimated number of persons exposed	Range of doses to exposed individ- uals ² (per reactor year)	Cumulative dose to exposed popu- lation (per reactor year) ³
Transportation workers	200	0.01 to 300 millirem	4 man-rem.
Onlookers		0.003 to 1.3 millirem	3 man-rem.

Accidents in Transport

	Environmental risk
Radiological effects	Small ⁴ 1 fatal injury in 100 reactor years; 1 nonfatal injury in 10 reactor years; \$475 property damage per reactor year.

¹ Data supporting this table are given in the Commission's "Environmental Survey of Transportation of Radioactive Materials to and from Nuclear Power Plants," WASH-1238, December 1972, and Supp. 1 NUREG-75/038 April 1975. Both documents are available for inspection and copying at the Commission's Public Document Room, 2120 L Street NW., Washington, DC and may be obtained from National Technical Information Service, Springfield, VA 22161. WASH-1238 is available from NTIS at a cost of \$5.45 (microfiche, \$2.25) and NUREG-75/038 is available at a cost of \$3.25 (microfiche, \$2.25).

²The Federal Radiation Council has recommended that the radiation doses from all sources of radiation other than natural background and medical exposures should be limited to 5,000 millirem per year for individuals as a result of occupational exposure and should be limited to 5000 millirem per year for individuals more production. The dose to individuals due to aver

[49 FR 9381, Mar. 12, 1984; 49 FR 10922, Mar. 23, 1984, as amended at 53 FR 43420, Oct. 27, 1988]

§51.53 Postconstruction environmental reports.

(a) General. Any environmental report prepared under the provisions of this section may incorporate by reference any information contained in a prior environmental report or supplement thereto that relates to the production or utilization facility or any information contained in a final environmental document previously prepared by the NRC staff that relates to the production or utilization facility. Documents that may be referenced include, but are not limited to, the final environmental impact statement; supplements to the final environmental impact statement, including supplements prepared at the license renewal stage; NRC staff-prepared final generic environmental impact statements; and environmental assessments and records of decisions prepared in connection with the construction permit, the operating license, and any license amendment for that facility.

(b) Operating license stage. Each applicant for a license to operate a production or utilization facility covered by §51.20 shall submit with its application a separate document entitled "Supplement to Applicant's Environmental Report—Operating License Stage," which will update "Applicant's Environmental Report-Construction Permit Stage." Unless otherwise required by the Commission, the applicant for an operating license for a nuclear power reactor shall submit this report only in connection with the first licensing action authorizing full-power operation. In this report, the applicant shall discuss the same matters described in §§ 51.45, 51.51, and 51.52, but only to the extent that they differ from those discussed or reflect new information in addition to that discussed in the final environmental impact statement prepared by the Commission in connection with the construction permit. No discussion of need for power, or of alternative energy sources, or of alternative sites for the facility, or of any aspect of the storage of spent fuel for the facility within the scope of the generic determination in §51.23(a) and in accordance with §51.23(b) is required in this report.

(c) Operating license renewal stage. (1) Each applicant for renewal of a license to operate a nuclear power plant under part 54 of this chapter shall submit

sure and should be limited to 500 millirem per year for individuals in the general population. The dose to individuals due to average natural background radiation is about 130 millirem per year.

3 Man-rem is an expression for the summation of whole body doses to individuals in a group. Thus, if each member of a population.

⁽⁵⁰⁰ millirem) each, the total man-rem dose in each case would be 1 man-rem.

4 Athough the environmental risk of radiological effects stemming from transportation accidents is currently incapable of being numerically quantified, the risk remains small regardless of whether it is being appiled to a single reactor or a multireactor site.